

CAT-40G • CAT-40G-SA

The CAT-40G is the ideal Rewinder if you require a significant amount of torque, and/or if you require the ability to precisely stop the Rewinder without any potential material overrun. This heavy-duty gear-driven Rewinder brings an impressive amount of power to your project, and is designed for continuous 24/7 operation.



CAT-40G

Technical Specifications	CAT-40G	CAT-40G-SA ¹
Max Roll Diameter (in)	16 (406-mm)	
Core Diameter (in)	3 (76-mm)	
Max Media Width (in) ²	6 - 10 (152 - 254-mm)	
Max Roll Weight (lbs)	75 (34-kg)	
Dimensions-HWD (in)	19 x 16 x 18 (482 x 406 x 457-mm)	19 x 17 x 18 (482 x 432 x 457-mm)
Weight (lbs) ²	34 - 38 (15 - 17-kg)	35 - 39 (15.8 - 17.7-kg)
Max Speed (ips)	320 (8128-mm)	160 (4064-mm)
Min Speed (ips)	1 (25-mm)	2 (50-mm)
Max Torque (in-oz)	850	
Max RPM	485	
Number of Flanges	2	
Power Specifications	120-220VAC in, 24VDC 100W out	
Warranty	5 year limited warranty on Rewinder - 1 year limited warranty on Power Adaptor	
Available Options	<ul style="list-style-type: none"> • ADAPT-326 (6" Core Adaptor) • FOOTSWITCH 	<ul style="list-style-type: none"> • ADAPT-326 (6" Core Adaptor) • FOOTSWITCH

1. The **CAT-40G-SA** utilizes a dancer arm to automatically start and stop the rewind action, and is ideal for use with a printer.

2. Depends on whether you order the CHUCK, CHUCK-220, or CHUCK-10 model